DEWAN GLOBAL SERVICES SPC

C.R: 1457816 SULTANETE OF OMÁN

**SAFETY**

# CARGO RESTRAINT & LIFTING SOLUTIONS

Industrial Product Overview




**EDITION 01 / 2026 - REV. 02**

SULTANATE OF OMAN / INTERNATIONAL SUPPLY

01 / COMPANY

# International supply. Industrial focus.

Cargo restraint, lifting, industrial webbing and fall protection.

Dewan Global Services SPC coordinates product selection, technical requirements and international supply for industrial buyers. Each enquiry links the required configuration with commercial terms, documentation and delivery planning.



## PRODUCTION NETWORK

Weaving and webbing production environment. Production partner facility shown for reference.

## BASED IN OMAN. CONNECTED INTERNATIONALLY.

Supporting Oman, Spain, the Gulf and international markets.

02 / PRODUCT RANGE

# The range at a glance.

Select by application, then confirm the exact configuration.

04-05 **Cargo restraint**
Ratchet straps, compact buckles and tensioning variants

06 **Flat woven slings**
Eye slings for general lifting requirements

07 **Round slings**
Endless polyester fibre construction

08 **One-way slings**
Eyed and endless forms for defined handling cycles

09-10 **Industrial webbing**
Polyester webbing in multiple widths and weight designations

11-12 **Fall protection**
Full-body harnesses, lanyards and connectors

13-15 **Selection & supply**
Applications, documentation and quotation requirements

Branded textile images are digitally recreated visualisations, not verified product photographs. Final construction, branding, ratings and availability require confirmation by reference.

03 / CARGO RESTRAINT

# Ratchet lashing straps

Webbing assemblies for securing cargo during transport.




## ASSEMBLY CONFIGURATIONS

Four configurations shown in the original range, recreated with Dewan branding.

Confirm the ratchet mechanism, hook geometry, working length and anchor compatibility for the selected assembly.

| WIDTH | SOURCE CLASS* | LENGTH OPTIONS |
|---|---|---|
| 25 mm | 0.8 t | 3 / 4 / 5 m |
| 35 mm | 2 t | 6 / 8 m |
| 50 mm | 2 t | 8 / 10 / 12 m |
| 50 mm | 5 t | 8 / 10 / 12 m |
| 75 mm | 10 t | 10 / 12 m |

* Original range designations. The source does not establish whether these values mean LC or breaking strength. They must not be used as working capacities.

Digitally recreated brand visuals. Cargo restraint only; not for lifting. Confirm LC, STF, SHF and the rated assembly label before order.

04 / CONFIGURATION

# Eight tensioning variants

Each pictured variant is retained as a separate range entry.




LEFT TO RIGHT / TOP TO BOTTOM

**01 Mini buckle**

No rating stated

**02 Mini ratchet**

No rating stated

**03 Medium-size ratchet**

Source designation: 1 t

**04 Standard ratchet**

Source designation: 2 t

**05 Economy ratchet**

Source designation: 2 t

**06 Standard heavy ratchet**

Source designation: 5 t

**07 Ergonomic ratchet**

Source designation: 5 t

**08 Large ratchet**

Source designation: 10 t

Digitally recreated brand visuals. Source tonnage designations are not confirmed LC or breaking strength. The medium 1 t designation is not equated with the separate 0.8 t table entry.

05 / LIFTING

# Flat woven webbing slings

A flat textile construction with sewn eyes for lifting applications.




| | | | |
|---|---|---|---|
| **Violet / 1 t** | **Green / 2 t** | **Yellow / 3 t** | **Grey / 4 t** |
| **Red / 5 t** | **Brown / 6 t** | **Blue / 8 t** | **Orange / 10 t** |

## ADDITIONAL CATALOGUE LISTINGS: 16 t / 20 t

Listed in the general table; product family, reference and availability require confirmation.

> Digitally recreated brand visuals. Values are source range designations, not an approved lifting chart. Confirm WLL, length, eyes and traceability before use.

06 / LIFTING

# Round slings

Endless load-bearing polyester fibres within a protective cover.




**Violet / 1 t** **Green / 2 t** **Yellow / 3 t**

## GENERAL SLING LENGTH ENQUIRIES

The general source table lists 1 / 2 / 3 / 4 / 5 / 6 / 8 / 10 / 12 / 14 / 15 / 16 / 18 m, depending on class. These are enquiry options, not confirmed lengths for every round sling.

Digitally recreated brand visuals. Confirm product-specific WLL, effective length, permitted lifting mode and operating environment before use.

07 / DEFINED HANDLING CYCLES

# One-way slings

Eyed and endless configurations for specified handling operations.




## EYED

A flat sling with end eyes. Confirm eye dimensions and connection requirements.

## ENDLESS

A closed loop configuration. Confirm effective length and the intended arrangement.

### FOR EXPORT, PRE-SLINGING AND PLANNED HANDLING

Define the load, handling stages and disposal point before quotation. Supply is subject to an approved application and reference-specific data.

> Digitally recreated brand visuals. One-way slings are for defined handling cycles. Confirm capacity, safety factor, permitted use and retirement criteria.

08 / INDUSTRIAL MATERIALS

# Polyester webbing

Ten listed material variants, shown individually.




LEFT TO RIGHT / TOP TO BOTTOM

**01 25 mm / 22 g**

**02 35 mm / 30 g**

**03 48 mm / 44 g**

**04 50 mm / 65 g**

**05 50 mm / 75 g**

**06 50 mm / 80 g**

**07 50 mm / 100 g**

**08 50 mm / 110 g**

**09 50 mm / 125 g**

**10 75 mm / 179 g**

Digitally recreated brand visuals. Gram values are source designations, not confirmed g/m. Raw webbing is not a rated sling or lashing assembly. See the material table opposite.

09 / MATERIAL SELECTION

# Widths & listed variants

All ten material variants shown in the supplied range.

| WIDTH | LISTED WEIGHT DESIGNATION | COLOUR |
|---|---|---|
| 25 mm | 22 g | To specification |
| 35 mm | 30 g | To specification |
| 48 mm | 44 g | To specification |
| 50 mm | 65 g | To specification |
| 50 mm | 75 g | To specification |
| 50 mm | 80 g | To specification |
| 50 mm | 100 g | To specification |
| 50 mm | 110 g | To specification |
| 50 mm | 125 g | To specification |
| 75 mm | 179 g | To specification |

## CUSTOM COLOUR ENQUIRIES

Provide the required colour reference, quantity and intended application. Availability and minimum quantities are confirmed with the offer.

> The source lists weight in grams without defining the length basis. These are range identifiers, not confirmed g/m values. Confirm the measurement basis before ordering.

10 / WORK AT HEIGHT

# Full-body harnesses

Equipment selection starts with the complete protection system.

## PRODUCT OVERVIEW

The illustrated harness uses polyester webbing and adjustable buckles, with one rear D-ring, two rings on the waist support and adjustable buckles.



## 45 mm

Webbing width stated for the illustrated range.

## MATCH THE MODEL TO THE TASK

Confirm the exact model, fit, permitted attachment points, intended use and compatible system components. Product-specific instructions and conformity documents are required before selection.

> Do not assume every ring is a fall-arrest attachment point. The function of each attachment must be established from the exact model instructions.

11 / SYSTEM COMPONENTS

# Lanyards & connectors

Assess compatibility as part of the complete work-at-height system.





## CONNECTORS

Confirm type, locking mechanism, gate opening, strength markings and compatibility with the harness and anchor.

## LANYARDS

Confirm intended function, construction, length, terminations and whether energy absorption is required by the selected system.

### DOCUMENT THE COMPLETE CONFIGURATION

A component illustration is not evidence of a complete fall-arrest system.

The supplied range does not establish model-specific performance for these components. Ratings and permitted combinations require technical confirmation.

12 / APPLICATIONS

# Built around the operation.

Supply enquiries across transport, ports and industrial projects.

## TRANSPORT & LOGISTICS

Road loads, machinery movements and warehouse dispatch.

Ratchet assemblies and webbing specifications

## PORTS & MARINE SUPPLY

Cargo handling and port-side supply requirements.

Port slings / port ropes: reference and specification on enquiry

## CRANES & INDUSTRIAL LIFTING

Equipment positioning and planned lifting operations.

Flat woven and round sling selection

## EPC, CONSTRUCTION & ENERGY

Project procurement and maintenance requirements.

Load restraint, lifting and work-at-height equipment

> For coils, sharp-edged steel or sensitive surfaces, specify contact geometry and protective measures. Special applications require a competent technical assessment.

13 / DOCUMENTATION

# Confirm the product. Then confirm the order.

Technical requirements and evidence are checked by reference.

| PRODUCT FAMILY | DOCUMENTS / DATA TO CONFIRM |
|---|---|
| Web lashing assemblies | LC, STF, SHF, end fittings, label and instructions |
| Flat woven slings | WLL, length, eyes, construction and traceability |
| Round slings | WLL, effective length, cover and instructions |
| One-way slings | Rated use, handling cycle and retirement criteria |
| Industrial webbing | Dimensions, tensile data and measurement basis |
| Fall protection | Exact model, conformity documents and instructions |

## STANDARDS BY PRODUCT TYPE

EN 12195-2: web lashing assemblies
EN 1492-1: flat woven webbing slings
EN 1492-2: round slings
EN 361: full-body harnesses

> These references identify the relevant product categories; they are not declarations of conformity. Evidence is confirmed for the exact product and destination.

14 / REQUEST A QUOTATION

# TELL US THE LOAD. WE DEFINE THE REQUIREMENT.

A clear brief supports a precise technical and commercial offer.

**01** **THE LOAD**

Cargo type, weight, dimensions, centre of gravity and contact surfaces.

**02** **THE OPERATION**

Application, method of use, required capacity and operating conditions.

**03** **THE PRODUCT**

Family, length, quantity, hook or termination and preferred configuration.

**04** **THE DELIVERY**

Country, delivery location, requested date and preferred delivery terms.

**05** **THE EVIDENCE**

Required certificates, specifications, photographs and drawings.

**COMMERCIAL ENQUIRIES**

**info@dewangs.com**

dewangs.com

DEWAN GLOBAL SERVICES SPC

C.R: 1457816 SULTANETE OF OMÁN

# SECURE EVERY MOVE.

Cargo restraint, lifting and industrial webbing solutions supported by structured sourcing and product-level documentation.


**COMMERCIAL ENQUIRIES**

## DEWAN GLOBAL SERVICES SPC

C.R. 1457816 | Sultanate of Oman

info@dewangs.com

dewangs.com



EDITION 01 / REV. 02 / 25 SEPTEMBER 2026